



# COMPOUND DATA SHEET

Parker O-Ring & Engineered Seals Division United States

## MATERIAL REPORT

DATE: October 2000

**TITLE:** General evaluation of Parker Compound FF350-75.

**PURPOSE:** To obtain general data for Parker Compound FF350-75.

**CONCLUSION:** Parker Compound FF350-75 is an ultra high temperature and clean perfluorinated elastomer.

Recommended temperature limits: 5 to 608°F

### Recommended For

Aliphatic and aromatic hydrocarbons  
Chlorinated hydrocarbons  
Polar solvents (acetone, methylethylketone, dioxane)  
Inorganic and organic acids  
Water and steam  
High vacuum with minimal loss in weight  
Petroleum oil  
Wet/dry chlorine

### Not Recommended For

Fluorinated refrigerants (R11, 12, 13, 113, 114)  
Uranium hexafluoride  
Molten Metals  
Gaseous and alkali metals



Contact Us

Parker O-Ring & Engineered Seals Division  
2360 Palumbo Drive  
Lexington, Kentucky 40509  
(859) 269-2351



# COMPOUND DATA SHEET

Parker O-Ring & Engineered Seals Division United States

## REPORT DATA

FF350-75 2-214

Original Physical Properties

Hardness, Shore A, pts.	74
Tensile Strength, MPa	16
Elongation, %, min.	125
Modulus @ 100% Elongation, MPa	9.4

Compression Set, 70 Hrs @ 200°C, ASTM D395 Method B

Permanent Set, %	13
------------------	----

Compression Set, 70 Hrs @ 260°C, ASTM D395 Method B

Permanent Set, %	26
------------------	----

Low Temperature Retraction, ASTM D1329

TR-10 in degrees C

Volume Change, 70 Hrs @ RT, ASTM D471

Acetone, % Volume Change	0.3
Methyl Ethyl Ketone, % Volume Change	0.2
Methanol, % Volume Change	0.2
Benzene, % Volume Change	0.3
Toluene, % Volume Change	0.3
Dichloromethane, % Volume Change	0.5
Chloroform, % Volume Change	0.5
Ethyl Acetate, % Volume Change	0.4
MTBE, % Volume Change	0.3
Glacial Acetic Acid, % Volume Change	0.1
Conc. Phosphoric Acid, % Volume Control	0.1
50/50 by Volume, MEK/Methanol, % Volume Change	0.6
Tetrahydrofuran (THF), % Volume Change	0.4
Styrene Monomer, % Volume Change	0.2
Methyl Methacrylate Monomer, % Volume Change	0.3

Parker O-Ring & Engineered Seals Division  
2360 Palumbo Drive  
Lexington, Kentucky 40509  
(859) 269-2351